

## GPS uncased active antennas



<b>Menge:</b>	unbegrenzt
<b>Mindestabnahme:</b>	quote
<b>Verkaufseinheit:</b>	Stück
<b>Preis:</b>	0 € (zzgl. 0 Mwst €/Stück) = 0 €/Stück
<b>Mwst:</b>	17 %
<b>Vesandart:</b>	
<b>Zahlungsart:</b>	
<b>Angebots Datum:</b>	14.04.2005

### Features:

Center Frequency :1575.42MHZ+3MHZ  
V.S.W.R: 1.5:1  
Band Width : +-3MHZ  
Attenuation: Centre frequency +-100MHZ>30db  
Impedence: 50ohm  
Peak Gain: >3dbic based on 7cm x 7cm ground plane  
Gain coverage : >-4dbic at -90temp (over 75% Volume)  
polarization : RHCP  
LNA Gain(without cable) 27db Typical  
Noise Figure :1.5 db  
DC current : 12mA (max)  
mount :Magneticbase / stick with glue  
Cable: RG174 5 meters long Optional  
Connector:SMA,SMB,MCX,MMCX,Optional  
Humidity:95%~100%RH  
Working Temp: -40temp~+85temp  
Storge Temp:-40temp~+100temp  
100%Waterproof